



# TACKY SURFACE COATING

## Water-based Tacky Coating

### PRODUCT DESCRIPTION

**Orapi Applied Tacky Surface Coating** is a clear aqueous solution of specially selected resins and tackifiers formulated to give a non-drying, at ambient temperature, tacky coating to paint spray booth walls. The applied tacky film will collect and hold dust, paint overspray etc thus greatly assisting in keeping the spray booth area clean and free of airborne particles.

When contaminated **Orapi Applied Tacky Surface Coating** can be washed off with water and a fresh coat applied immediately.

### FEATURES & BENEFITS

- Clear coating
- Solvent free – Water based product.
- Long lasting tacky film.
- Water washable – easily cleaned.
- Can be reapplied immediately
- High degree of dust and paint overspray retention.
- Keeps booth free of airborne contaminants.
- Improved finish quality.
- Retain booths in 'as new' condition.

### DIRECTIONS FOR USE

For **New Booths** which are internally painted or plastic coated it is recommend that the surface is pre-washed with a 2-5% solution of **Orapi Applied Aquabrite** to remove any grease or oil contamination and the surface dried before application of **Orapi Applied Tacky Surface Coating** to give an unbroken film.

**SPRAY:** Use a spray gun with a fluid tip of 0.635-1.8mm (0.0025' – 0.007').

A single pass using a fairly wide fan should give sufficient coverage, ensuring that a continuous coating is applied leaving no uncoated areas.

#### Manufacturing site and registered office

Orapi Applied Limited  
Spring Road, Smethwick, West Midlands  
B66 1PT, United Kingdom  
Tel: +44 (0) 121 525 4000  
Fax: +44 (0) 121 525 4919  
Info@orapiapplied.com



## PRODUCT DATA SHEET



# D4512

### DIRECTIONS FOR USE - Continued

**BRUSH:** Apply a thin coat only, avoid runs and dripping.

**ROLLER:** As single coat is adequate.

Wash application equipment with water after use.

**Orapi Applied Tacky Surface Coating** is suitable for application to most factory finished paint spray booths where the paintwork may be 2-pack polyurethane, 2-pack epoxy or other stove converted paint finishes. Care should be taken and patch testing carried out if applying to "uncured" paint finishes i.e. cellulose, household paints etc particularly in low bake applications.

In Spray Bake booths where temperatures of 50-80°C are regularly attained **Orapi Applied Tacky Surface Coating** will need to be removed and replaced more often, as it will eventually dry out and become coated with paint overspray making it more difficult to remove. The coating will remain effective for up to 50hrs at low bake temperatures and should be renewed every 2-4 weeks in most circumstances, either by over-spraying with fresh product or by complete removal and re-application.

### PHYSICAL CHARACTERISTICS

Appearance:	Opaque Liquid
Viscosity:	70-90 second Flow Cup No.4
Specific Gravity:	1.07 – 1.09
Solids Content:	< 25%
Coverage:	8-10m <sup>2</sup> @ 30μ film thickness
Flashpoint:	Non-flammable
Shelf Life:	24 months from date of manufacture

### SPECIAL STORAGE

Store in a dry place at ambient temperatures. Protect from freezing.

### HEALTH AND SAFETY

Refer to Material Safety Data Sheet for further information.

### PACKAGING

Pack size:	A4512-4X5	4 X 5L Container
	A4512-25	25L Drum

#### Manufacturing site and registered office

Orapi Applied Limited  
Spring Road, Smethwick, West Midlands  
B66 1PT, United Kingdom  
Tel: +44 (0) 121 525 4000  
Fax: +44 (0) 121 525 4919  
Info@orapiapplied.com

2 / 2

A4512 - TDS TACKY SURFACE COATING – 06/06/19  
ORAPI® cannot know about every application for which the products are used nor their conditions of use. ORAPI® cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case.