



DRIVING SURFACE PERFECTION

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
SDS Ref. (EU): BAR-SDS  
Issue date: 7/13/2015 Revision date: 12/3/2020 Supersedes version of: 8/26/2020 Version: 6.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : BARCOAT QUICK DRYING ISOLATOR  
UFI : QH30-20YS-E004-6U5C  
Product code : BAR/1  
Product group : 1K Primer

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
Use of the substance/mixture : Coatings and paints, thinners, paint removers  
Function or use category : Primer

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

U-POL Limited  
Denington Road  
NN8 2QH Wellingborough - United Kingdom  
T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### Importer

U-POL Netherlands B.V.  
Hoogoorddreef 15  
1101BA Amsterdam - Netherlands  
T +31 20 240 2216  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours ( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225  
Serious eye damage/eye irritation, Category 2 H319  
Full text of H-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes serious eye irritation.

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. — No smoking.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P264 - Wash hands thoroughly after handling.  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

Component	
ethanol; ethyl alcohol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propan-2-ol (67-63-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
methanol (67-56-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanol; ethyl alcohol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	10 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (EC Index-No.) 022-006-002 (REACH-no) 01-2119489379-17	5 – 10	Carc. 2, H351
methanol substance with a Community workplace exposure limit	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	< 2.5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	( 3 $\leq$ C < 10) STOT SE 2, H371 ( 10 $\leq$ C < 100) STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact	: Eye irritation.
------------------------------------	-------------------

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
Storage temperature : < 25 °C  
Storage area : Store in a well-ventilated place.  
Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Titanium dioxide
OEL TWA [1]	10 mg/m <sup>3</sup> total inhalable dust 4 mg/m <sup>3</sup> respirable dust
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> 4 mg/m <sup>3</sup>
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanol; ethyl alcohol (64-17-5)	
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Ethanol [Ethyl alcohol]
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>methanol (67-56-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Methanol
IOEL TWA	260 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
Notes	Skin Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC COMMISSION DIRECTIVE 2006/15/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Methanol [Methyl alcohol]
OEL TWA [1]	260 mg/m <sup>3</sup>
OEL TWA [2]	200 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Methanol
BLV	15 mg/l Parameter: methanol - Medium: urine - Sampling time: End of shift - Notations: B (Background), Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Methanol
WEL TWA (OEL TWA) [1]	266 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	333 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	250 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>propan-2-ol (67-63-0)</b>	
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Isopropyl alcohol [Propan-2-ol]
OEL TWA [2]	200 ppm
OEL STEL [ppm]	400 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>ethanol; ethyl alcohol (64-17-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	1900 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	950 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - local effects, inhalation	950 mg/m <sup>3</sup>
Long-term - systemic effects, oral	87 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	114 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	206 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.96 mg/l
PNEC aqua (marine water)	0.79 mg/l
PNEC aqua (intermittent, freshwater)	2.75 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3.6 mg/kg dwt
PNEC sediment (marine water)	2.9 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.63 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	0.72 g/kg food

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>PNEC (STP)</b>	
PNEC sewage treatment plant	580 mg/l

  

<b>methanol (67-56-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	40 mg/kg bodyweight/day
Acute - systemic effects, inhalation	260 mg/m <sup>3</sup>
Acute - local effects, inhalation	260 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	260 mg/m <sup>3</sup>
Long-term - local effects, inhalation	260 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	8 mg/kg bodyweight/day
Acute - systemic effects, inhalation	50 mg/m <sup>3</sup>
Acute - systemic effects, oral	8 mg/kg bw/day
Acute - local effects, inhalation	50 mg/m <sup>3</sup>
Long-term - systemic effects, oral	8 mg/kg bw/day
Long-term - systemic effects, inhalation	50 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day
Long-term - local effects, inhalation	50 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	20.8 mg/l
PNEC aqua (marine water)	2.08 mg/l
PNEC aqua (intermittent, freshwater)	1540 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	77 mg/kg dwt
PNEC sediment (marine water)	7.7 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	3.18 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l

<b>propan-2-ol (67-63-0)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	140.9 mg/l

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC aqua (marine water)	140.9 mg/l
PNEC aqua (intermittent, freshwater)	140.9 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	28 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	160 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	2251 mg/l

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

##### Other skin protection

##### Materials for protective clothing:

Impermeable clothing

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment



# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Appearance	: Liquid.
Odour	: alcoholic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: > 35 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: 19 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Miscible with water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 1.15 (1.14 – 1.16) g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

VOC content : 473 g/l

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 473 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

#### carbon black (1333-86-4)

LD50 oral rat	> 8000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))

#### iron(III) oxide (1309-37-1)

LD50 oral rat	> 10000 mg/kg bodyweight (Rat, Male, Experimental value, Oral)
---------------	--

#### dolomite (16389-88-1)

LD50 oral rat	> 2000 mg/kg (OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), rat, female, Experimental value)
---------------	---

#### magnesium carbonate (546-93-0)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
---------------	---

#### bis(2-ethylhexyl) terephthalate (6422-86-2)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: other:TSCA FHSA Regulations (1979): 16 CFR Part 1500.40 (Hazardous Substances and Articles, Administration and Enforcement Regulations)
---------------	---

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ethanol; ethyl alcohol (64-17-5)</b>	
LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse
LD50 dermal rabbit	> 15800 mg/kg bodyweight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	125 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

<b>methanol (67-56-1)</b>	
LD50 oral rat	1187 – 2769 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))

<b>propan-2-ol (67-63-0)</b>	
LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	16400 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

<b>shellac (9000-59-3)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg

<b>quartz (14808-60-7)</b>	
LD50 oral rat	> 500 mg/kg

<b>tris(2-butoxyethyl) phosphate (78-51-3)</b>	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 6.4 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

<b>silicon dioxide, amorphous (7631-86-9)</b>	
LD50 oral rat	> 10000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Dermal)

<b>butyl glycolether (111-76-2)</b>	
LD50 oral rat	1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat [ppm]	450 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Female, Experimental value)

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>talco (14807-96-6)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.1 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 15 day(s))

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified.

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>ethanol; ethyl alcohol (64-17-5)</b>	
IARC group	1 - Carcinogenic to humans

<b>propan-2-ol (67-63-0)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

<b>methanol (67-56-1)</b>	
NOAEL (animal/male, F0/P)	< 1000 mg/kg bodyweight Animal: mouse, Animal sex: male

STOT-single exposure : Not classified

<b>methanol (67-56-1)</b>	
STOT-single exposure	Causes damage to organs.

<b>propan-2-ol (67-63-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

<b>ethanol; ethyl alcohol (64-17-5)</b>	
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

<b>butyl glycoether (111-76-2)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard : Not classified

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7)

LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	$\geq 2.92$ mg/l Test organisms (species): Daphnia magna Duration: '21 d'

#### ethanol; ethyl alcohol (64-17-5)

LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas
EC50 72h - Algae [1]	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

#### methanol (67-56-1)

LC50 - Fish [1]	15400 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	$\approx 22000$ mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

#### propan-2-ol (67-63-0)

LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

### 12.2. Persistence and degradability

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] (13463-67-7)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ThOD	Not applicable (inorganic)
------	----------------------------

<b>ethanol; ethyl alcohol (64-17-5)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.7 g O <sub>2</sub> /g substance
ThOD	2.1 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.43

<b>methanol (67-56-1)</b>	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance

<b>propan-2-ol (67-63-0)</b>	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.23 g O <sub>2</sub> /g substance
ThOD	2.4 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
Bioaccumulative potential	Not bioaccumulative.

<b>ethanol; ethyl alcohol (64-17-5)</b>	
BCF - Fish [1]	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	-0.31 (Experimental value)
Bioaccumulative potential	Not bioaccumulative.

<b>methanol (67-56-1)</b>	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

<b>propan-2-ol (67-63-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
Ecology - soil	Low potential for mobility in soil.

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanol; ethyl alcohol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Partition coefficient n-octanol/water (Log Koc)	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.

methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	0.088 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

propan-2-ol (67-63-0)	
Surface tension	0.021 N/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Results of PBT and vPvB assessment

Component	
ethanol; ethyl alcohol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propan-2-ol (67-63-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
methanol (67-56-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

### 14.1. UN number or ID number

UN-No. (ADR)	: UN 1263
UN-No. (IMDG)	: UN 1263

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

UN-No. (IATA) : UN 1263  
UN-No. (ADN) : UN 1263  
UN-No. (RID) : UN 1263

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : PAINT  
Proper Shipping Name (IMDG) : PAINT  
Proper Shipping Name (IATA) : Paint  
Proper Shipping Name (ADN) : PAINT  
Proper Shipping Name (RID) : PAINT  
Transport document description (ADR) : UN 1263 PAINT, 3, II, (D/E)  
Transport document description (IMDG) : UN 1263 PAINT, 3, II  
Transport document description (IATA) : UN 1263 Paint, 3, II  
Transport document description (ADN) : UN 1263 PAINT, 3, II  
Transport document description (RID) : UN 1263 PAINT, 3, II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3

:



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3

:



#### IATA

Transport hazard class(es) (IATA) : 3  
Danger labels (IATA) : 3

:



#### ADN

Transport hazard class(es) (ADN) : 3  
Danger labels (ADN) : 3

:



#### RID

Transport hazard class(es) (RID) : 3  
Danger labels (RID) : 3

:





# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640D, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

#### Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

#### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

#### Inland waterway transport

Classification code (ADN)	: F1
---------------------------	------

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special provisions (ADN) : 163, 367, 640D, 650  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E2  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : F1  
Special provisions (RID) : 163, 367, 640D, 650  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001, IBC02, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP8, TP28  
Tank codes for RID tanks (RID) : LGBF  
Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE7  
Hazard identification number (RID) : 33

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:		
Reference code	Applicable on	Entry title or description
3(a)	BARCOAT QUICK DRYING ISOLATOR ; ethanol ; methanol ; propan-2-ol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	BARCOAT QUICK DRYING ISOLATOR ; ethanol ; methanol ; propan-2-ol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
40.	BARCOAT QUICK DRYING ISOLATOR ; ethanol ; methanol ; propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
69.	methanol	Methanol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 473 g/l

#### 15.1.2. National regulations

No additional information available

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2

# BARCOAT QUICK DRYING ISOLATOR

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H371	May cause damage to organs.

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).