



## PROPEEL

**White, solvent based peelable coating**

### PRODUCT DESCRIPTION

GRAMOS® PROPEEL is a white pigmented temporary protective coating designed for application to all smooth clean metal spray booth walls in order to provide an easy method of booth maintenance. The dried film is readily peelable and enables even heavy overspray deposits to be quickly and cleanly removed.

Exposed areas can then be touched in or entire area re-sprayed as necessary. By providing a white light reflective surface better working conditions are obtained making for a consistent achievement of high quality work.

### FEATURES & BENEFITS

GRAMOS® PROPEEL provides a dry plastic temporary coating that will facilitate 'capture & containment' of even the heaviest paint overspray deposits that can then be quickly and easily removed by peeling off the coating for disposal during routine booth maintenance.

G4602 should be applied to clean bare metal (normally galvanised), unpainted substrates and removed, depending on the degree of overspray contamination, every 3 months prior to re-application.

- Strong easily peelable film.
- Is easy to apply.
- Has a dense white film – Excellent background reflection.
- Reduces maintenance time.
- Heavily contaminated areas may be cut and painted in.

### DIRECTIONS FOR USE

Use as supplied, stirring thoroughly before use to disperse and settled pigment.

Apply by conventional spraying techniques using normal pressure spraying equipment, pot pressure of 20 psi (1-2 bar), air pressure 40-60 psi (3-4 bar); and using a 70 thou (1.78mm) tip, with appropriate air cap and needle.

#### Manufacturing site and registered office

Orapi Applied Limited  
Spring Road, Smethwick, West Midlands  
B66 1PT, United Kingdom  
Tel: +44 (0) 121 525 4000  
Fax: +44 (0) 121 525 4919  
Info@orapiapplied.com



## PRODUCT DATA SHEET



# G4602

Apply a double pass, wet on wet, to give a dense white film. Do not dry spray as this may lead to some film shrinkage and poor peelability.

Do not use suction feed guns.

After use clean all equipment with G4161 Propeel Thinners.

### NOTE

Solvent based peelable coatings are not generally suitable for application to painted, plastic or lacquered surfaces and **must** be carefully patch tested before use to ensure no surface attack occurs and the product remains easily peelable after normal usage conditions.

Any use of the product on solvent sensitive surfaces where natural evaporation of the solvent may be retarded can lead to aggravated solvent attack, for instance, seepage under a mask.

### COVERAGE

2-3 square metres/litre, at 2-3 thou (0.05 – 0.076mm) dry film thickness.

## SPECIAL STORAGE

Store in a cool place in compliance with Petroleum Consolidation Act 1928 and amendments and/or Dangerous Substances and Explosive Atmosphere Regulations.

Protect from Freezing.

## HEALTH AND SAFETY

Refer to Material Safety Data Sheet for further information.

## PACKAGING

Pack size:	G4692-4X5	4 x 5L Container
	G4602-25	25L Drum

### Manufacturing site and registered office

Orapi Applied Limited  
Spring Road, Smethwick, West Midlands  
B66 1PT, United Kingdom  
Tel: +44 (0) 121 525 4000  
Fax: +44 (0) 121 525 4919  
Info@orapiapplied.com

2 / 2

G4602 - PROPEEL - 21/11/2017

ORAPI® cannot know about every application for which the products are used nor their conditions of use. ORAPI® cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case.