

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019


Revised Date: 07/06/2024

Version: 11

1. PRODUCT AND COMPANY IDENTIFICATION

1.1	Product Code	Polyurethane Clear Lacquer UMX091
	Other means of identification	WO30090M - Matt 10% 5L WO30091M - Matt 10% 20L WO30090SM - Semi Matt 20% 5L
1.2	Relevant identified uses of the substance or mixture and uses advised against	Relevant uses: Product for varnishing wood. For industrial use only. Uses advised against: All uses not specified in this section or in section 7.3
1.3	Name, Address, Telephone Number of the chemical manufacturer	Ultrimax Coatings Ltd Shaw Lane Industrial Estate, Ogden Road, Doncaster, DN2 4SE 01302 856666
1.4	Emergency phone number	01302 856666

2. HAZARD(S) IDENTIFICATION

2.1	Classification of the substance or mixture	<p>Classification of this product has been carried out in accordance with CLP Regulation(EC) No 1272/2008.</p> <p>Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412</p> <p>Carc. 2: Carcinogenicity, Category2, H351</p> <p>Eye Irrit. 2: Eye irritation, Category 2, H319</p> <p>Flam. Liq. 3: Flammable liquids, Category 3, H226</p> <p>Repr. 2: Reproductive toxicity, Category2, H361d</p> <p>Skin Irrit. 2: Skin irritation, Category 2, H315</p> <p>STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category2, H373</p> <p>STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336</p> <p>STOT SE 3: Respiratory tract toxicity, single exposure, Category3, H335</p>
	CLP Regulation (EC) No 1272/2008	
2.2	Label elements	<p>Danger</p> 
	CLP Regulation (EV) No 1272/2008	
	Hazard statements	
		<p>H226 - Flammable liquid and vapour.</p> <p>H315 - Causes skin irritation.</p> <p>H319 - Causes serious eye irritation.</p> <p>H335 - May cause respiratory irritation.</p> <p>H336 - May cause drowsiness or dizziness.</p> <p>H351 - Suspected of causing cancer.</p> <p>H361d - Suspected of damaging the unborn child.</p> <p>H373 - May cause damage to organs through prolonged or repeated exposure.</p> <p>H412 - Harmful to aquatic life with long lasting effects.</p>

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200




Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

2.2	Precautionary statements	<p>P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.</p> <p>P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313: IF exposed or concerned: Get medical advice/attention.</p> <p>P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.</p> <p>P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.</p>
	Supplementary information	EUH208: Contains Fatty acids, tall-oil, compds. with oleylamine. May produce an allergic reaction.
	Substances that contribute to the classification	Reaction mass of ethylbenzene and xylene; Ethyl acetate; N-butyl acetate; Propyl acetate
	UFI	PAJ6-E0R4-7005-7GWE
2.3	Other hazards	<p>Product does not meet PBT/vPvB criteria</p> <p>Endocrine-disrupting properties: The product does not meet the criteria.</p>

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1	Substances	Not applicable (N/A)		
	Mixtures	Mixture composed of additives and long oil alkyd resin in solvents		
	Chemical description	In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:		
3.2	Components	Identification	Chemical name/Classification	Concentration
		CAS: N/A EC: 905-588-0 Index: N/A REACH: 01-2119488216-32-XXXX	Reaction mass of ethylbenzene and xylene ⁽¹⁾ Self Classified 	25-<50%
		Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
		CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	Toluene ⁽¹⁾ Self Classified 	10-<25%
		Regulation 1272/2008	Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	
		CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	N-butyl acetate ⁽¹⁾ ATP CLP00 	10-<25%
Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning			

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

		Identification	Chemical name/Classification	Concentration
3.2	Components	CAS: 108-10-1 EC: 203-550-1 Index: 606-004-00-4 REACH: 01-2119473980-30-XXXX	4-methylpentan-2-one ⁽¹⁾ ATP ATP17	5-<10%
			Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
		CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⁽¹⁾ Self-Classified	2.5-<5%
			Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
		CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	Butanone ⁽¹⁾ ATP CLP00	0.25-<2.5%
			Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
		CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	Ethyl acetate ⁽¹⁾ ATP CLP00	0.25-<2.5%
			Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
		CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	Toluene ⁽²⁾ ATP CLP00	<0.1%
			Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	
CAS: 85711-55-3 EC: 288-315-1 Index: Non-applicable REACH: 01-2119974148-28-XXXX	Fatty acids, tall-oil, compds. with oleylamine ⁽¹⁾ Self-Classified	<0.1%		
	Regulation 1272/2008 Eye Dam. 1: H318; Skin Sens. 1A: H317; STOT RE 2: H373 - Danger			
CAS: 95-63-6 EC: 202-436-9 Index: 601-043-00-3 REACH: 01-2119472135-42-XXXX	1,2,4-trimethylbenzene ⁽²⁾ ATP CLP00	<0.1%		
	Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning			
CAS: 98-82-8 EC: 202-704-5 Index: 601-024-00-X REACH: 01-2119473983-24-XXXX	Cumene ⁽²⁾ ATP ATP18	<0.1%		
	Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Carc. 1B: H350; Flam. Liq. 3: H226; STOT SE 3: H335 - Danger			

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in accordance to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

Components	<table border="1"> <thead> <tr> <th>Identification</th> <th>Chemical name/Classification</th> <th>Concentration</th> </tr> </thead> <tbody> <tr> <td>CAS: 108-67-8 EC: 203-604-4 Index: 601-025-00-5 REACH: 01-2120738996-34- XXXX</td> <td>Mesitylene⁽²⁾ ATP CLP000 </td> <td rowspan="2"><0.1%</td> </tr> <tr> <td>Regulation 1272/2008</td> <td>Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning</td> </tr> <tr> <td>CAS: 526-73-8 EC: 208-394-8 Index: Non-applicable REACH: Non-applicable</td> <td>1,2,3-trimethylbenzene⁽²⁾ Self-Classified </td> <td rowspan="2"><0.1%</td> </tr> <tr> <td>Regulation 1272/2008</td> <td>Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning</td> </tr> <tr> <td>CAS: Non-applicable EC: 905-588-0 Index: Non-applicable REACH: 01-2119539452-40- XXXX</td> <td>Reaction mass of ethylbenzene and xylene⁽²⁾ Self-Classified </td> <td rowspan="2"><0.1%</td> </tr> <tr> <td>Regulation 1272/2008</td> <td>Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger</td> </tr> </tbody> </table>	Identification	Chemical name/Classification	Concentration	CAS: 108-67-8 EC: 203-604-4 Index: 601-025-00-5 REACH: 01-2120738996-34- XXXX	Mesitylene ⁽²⁾ ATP CLP000	<0.1%	Regulation 1272/2008	Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning	CAS: 526-73-8 EC: 208-394-8 Index: Non-applicable REACH: Non-applicable	1,2,3-trimethylbenzene ⁽²⁾ Self-Classified	<0.1%	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	CAS: Non-applicable EC: 905-588-0 Index: Non-applicable REACH: 01-2119539452-40- XXXX	Reaction mass of ethylbenzene and xylene ⁽²⁾ Self-Classified	<0.1%	Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	<p>⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878</p> <p>⁽²⁾ Substance with a Union workplace exposure limit</p> <p>To obtain more information on the hazards of the substances consult sections 11, 12 and 16.</p>																
	Identification	Chemical name/Classification	Concentration																																	
	CAS: 108-67-8 EC: 203-604-4 Index: 601-025-00-5 REACH: 01-2120738996-34- XXXX	Mesitylene ⁽²⁾ ATP CLP000	<0.1%																																	
	Regulation 1272/2008	Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning																																		
CAS: 526-73-8 EC: 208-394-8 Index: Non-applicable REACH: Non-applicable	1,2,3-trimethylbenzene ⁽²⁾ Self-Classified	<0.1%																																		
Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning																																			
CAS: Non-applicable EC: 905-588-0 Index: Non-applicable REACH: 01-2119539452-40- XXXX	Reaction mass of ethylbenzene and xylene ⁽²⁾ Self-Classified	<0.1%																																		
Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger																																			
3.2	<table border="1"> <thead> <tr> <th>Identification</th> <th>Specific concentration limit</th> </tr> </thead> <tbody> <tr> <td>Mesitylene CAS: 108-67-8 EC: 203-604-4</td> <td>% (w/w) >=25: STOT SE 3 - H335</td> </tr> <tr> <td>Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0</td> <td>% (w/w) >=10: STOT RE 2 - H373</td> </tr> </tbody> </table>	Identification	Specific concentration limit	Mesitylene CAS: 108-67-8 EC: 203-604-4	% (w/w) >=25: STOT SE 3 - H335	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	% (w/w) >=10: STOT RE 2 - H373																													
Identification	Specific concentration limit																																			
Mesitylene CAS: 108-67-8 EC: 203-604-4	% (w/w) >=25: STOT SE 3 - H335																																			
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	% (w/w) >=10: STOT RE 2 - H373																																			
Other information	<p>Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:</p> <table border="1"> <thead> <tr> <th>Identification</th> <th colspan="2">Acute Toxicity</th> <th>Genus</th> </tr> </thead> <tbody> <tr> <td rowspan="3">Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0</td> <td>LD50 oral</td> <td>Not Relevant</td> <td></td> </tr> <tr> <td>LD50 dermal</td> <td>1100mg/kg</td> <td>Rat</td> </tr> <tr> <td>LC50 inhalation</td> <td>Not Relevant</td> <td></td> </tr> <tr> <td rowspan="3">Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0</td> <td>LD50 oral</td> <td>Not Relevant</td> <td></td> </tr> <tr> <td>LD50 dermal</td> <td>Not Relevant</td> <td></td> </tr> <tr> <td>LC50 inhalation</td> <td>11mg/L</td> <td>Rat</td> </tr> <tr> <td rowspan="3">Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0</td> <td>LD50 oral</td> <td>Not Relevant</td> <td></td> </tr> <tr> <td>LD50 dermal</td> <td>1100mg/kg</td> <td>Rat</td> </tr> <tr> <td>LC50 inhalation</td> <td>Not Relevant</td> <td></td> </tr> </tbody> </table>	Identification	Acute Toxicity		Genus	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	Not Relevant		LD50 dermal	1100mg/kg	Rat	LC50 inhalation	Not Relevant		Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	Not Relevant		LD50 dermal	Not Relevant		LC50 inhalation	11mg/L	Rat	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	Not Relevant		LD50 dermal	1100mg/kg	Rat	LC50 inhalation	Not Relevant		
Identification	Acute Toxicity		Genus																																	
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	Not Relevant																																		
	LD50 dermal	1100mg/kg	Rat																																	
	LC50 inhalation	Not Relevant																																		
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	Not Relevant																																		
	LD50 dermal	Not Relevant																																		
	LC50 inhalation	11mg/L	Rat																																	
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	Not Relevant																																		
	LD50 dermal	1100mg/kg	Rat																																	
	LC50 inhalation	Not Relevant																																		

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

4. FIRST AID MEASURES

4.1	Description of first aid measures	The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.
	By inhalation	Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.
	By skin contact	Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.
	By eye contact	Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.
	By ingestion/aspiration	Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.
4.2	Most important symptoms and effects, both acute and delayed	Acute and delayed effect are indicated in sections 2 and 11.
4.3	Indication of any immediate medical attention and special treatment needed	Not Relevant

5. FIREFIGHTING MEASURES

5.1	Extinguishing media	Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)
	Suitable extinguishing media	
	Unsuitable extinguishing media	Water Jet
5.2	Special hazards arising from the substance or mixture	As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.
5.3	Advice for firefighters	Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.
	Additional provisions	Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

6. ACCIDENTAL RELEASE MEASURES

6.1	Personal precautions, protective equipment and emergency procedures	Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.
	For Non-emergency personnel	
	For emergency responders	Wear protective equipment. Keep unprotected persons away. See section 8.
6.2	Environmental precautions	Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.
6.3	Methods and material for containment and cleaning up	It is recommended: Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.
6.4	Reference to other sections	See sections 8 and 13.

7. HANDLING AND STORAGE

7.1	Precautions for safe handling	<p>General Precautions for safe use</p> <p>Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods(section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.</p>
		<p>Technical recommendations for the prevention of fires and explosions</p> <p>Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition(mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.</p>

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

7.1	Precautions for safe handling	C	Technical recommendations on general occupational hygiene PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
		D	Technical recommendations to prevent environmental risks Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.
7.2	Conditions for safe storage, including any incompatibilities	A	Technical measures for storage Minimum Temp: 5°C Maximum Temp: 35°C
		B	General conditions for storage Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5.
7.3	Specific end use(s)		Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1	Control Parameters	Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation): Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:				
		Identification		Occupational exposure limits		
		2-methoxy-1-methylethyl acetate ⁽¹⁾ CAS: 108-65-6 EC: 203-603-9		IOELV (8h)	50ppm	275mg/m ³
				IOELV (STEL)	100ppm	550mg/m ³
		Toluene ⁽¹⁾ CAS: 108-88-3 EC: 203-625-9		IOELV (8h)	50ppm	192mg/m ³
				IOELV (STEL)	100ppm	384mg/m ³
		Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0		IOELV (8h)	50ppm	221mg/m ³
				IOELV (STEL)	100ppm	442mg/m ³
		Butanone CAS: 78-93-3 EC: 905-588-0		IOELV (8h)	200ppm	600mg/m ³
				IOELV (STEL)	300ppm	900mg/m ³
		Toluene ⁽¹⁾ CAS: 108-88-3 EC: 203-625-9		IOELV (8h)	50ppm	192mg/m ³
				IOELV (STEL)	100ppm	384mg/m ³
		Cumene ⁽¹⁾ CAS: 98-82-8 EC: 202-704-5		IOELV (8h)	20ppm	100mg/m ³
				IOELV (STEL)	50ppm	250mg/m ³
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9		IOELV (8h)	20ppm	100mg/m ³		
		IOELV (STEL)				
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0		IOELV (8h)	50ppm	221mg/m ³		
		IOELV (STEL)	100ppm	442mg/m ³		

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

	Control Parameters	Identification		Occupational exposure limits			
				IOELV (8h)	20ppm	100mg/m ³	
		Mesitylene CAS: 108-67-8 EC: 203-604-4		IOELV (STEL)			
		1,2,3-trimethylbenzene CAS: 526-73-8 EC: 208-394-8		IOELV (8h)	20ppm	100 mg/m ³	
				IOELV (STEL)			
		N-butyl acetate CAS: 123-86-4 EC: 204-658-1		IOELV (8h)	50ppm	241 mg/m ³	
				IOELV (STEL)	150ppm	723 mg/m ³	
		Ethyl acetate CAS: 141-78-6 EC: 205-500-4		IOELV (8h)	200ppm	734 mg/m ³	
				IOELV (STEL)	400ppm	1468 mg/m ³	
		4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1		IOELV (8h)	20ppm	83 mg/m ³	
				IOELV (STEL)	50ppm	208 mg/m ³	
		⁽¹⁾ Skin					
8.1	DNEL (Workers)	Identification		Short exposure		Long exposure	
				Systemic	Local	Systemic	Local
		Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	212mg/kg	N/A
			Inhalation	442mg/m ³	442mg/m ³	221mg/m ³	221mg/m ³
		Toluene CAS: 108-88-3 EC: 203-625-9	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	384mg/kg	N/A
			Inhalation	384mg/m ³	384mg/m ³	192mg/m ³	192mg/m ³
		N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	N/A	N/A	N/A	N/A
			Dermal	11mg/kg	N/A	11mg/kg	N/A
			Inhalation	600mg/m ³	600mg/m ³	300mg/m ³	300mg/m ³
		4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	11.8mg/kg	N/A
			Inhalation	208mg/m ³	208mg/m ³	83mg/m ³	83mg/m ³
		2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	769mg/kg	N/A
			Inhalation	N/A	550mg/m ³	275mg/m ³	N/A
		Butanone CAS: 78-93-3 EC: 201-159-0	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	1161mg/kg	N/A
			Inhalation	N/A	N/A	600mg/m ³	N/A
		Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	63mg/kg	N/A
			Inhalation	1468mg/m ³	1468mg/m ³	734mg/m ³	734mg/m ³
		Toluene CAS: 108-88-3 EC: 203-625-9	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	0.024mg/kg	N/A
			Inhalation	N/A	N/A	N/A	N/A

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

	Identification	Short exposure		Long exposure			
		Systemic	Local	Systemic	Local		
8.1	DNEL (Workers)	Fatty acids, tall-oil, compds. with oleylamine CAS: 85711-55-3 EC: 288-315-1	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	0.024mg/kg	N/A
			Inhalation	N/A	N/A	N/A	N/A
		1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	16171mg/kg	N/A
			Inhalation	100mg/m ³	100mg/m ³	100mg/m ³	100mg/m ³
		Cumene CAS: 98-82-8 EC: 202-704-5	Oral	N/A	N/A	N/A	N/A
			Dermal	N/A	N/A	15.4mg/kg	N/A
			Inhalation	N/A	250mg/m ³	100mg/m ³	N/A
	Mesitylene CAS: 108-67-8 EC: 203-604-4	Oral	N/A	N/A	N/A	N/A	
		Dermal	N/A	N/A	16171mg/kg	N/A	
		Inhalation	100mg/m ³	100mg/m ³	100mg/m ³	100mg/m ³	
	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	Oral	N/A	N/A	N/A	N/A	
		Dermal	N/A	N/A	212mg/kg	N/A	
		Inhalation	442mg/m ³	442mg/m ³	221mg/m ³	221mg/m ³	
	DNEL (General population)	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	Oral	N/A	N/A	12.5mg/kg	N/A
			Dermal	N/A	N/A	125mg/kg	N/A
			Inhalation	260mg/m ³	260mg/m ³	65.3mg/m ³	65.3mg/m ³
Toluene CAS: 108-88-3 EC: 203-625-9		Oral	N/A	N/A	8.13mg/kg	N/A	
		Dermal	N/A	N/A	336mg/kg	N/A	
		Inhalation	226mg/m ³	226mg/m ³	56.5mg/m ³	56.5mg/m ³	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1		Oral	2mg/kg	N/A	2mg/kg	N/A	
		Dermal	6mg/kg	N/A	6mg/kg	N/A	
		Inhalation	300mg/m ³	300mg/m ³	35.7mg/m ³	35.7mg/m ³	
4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1		Oral	N/A	N/A	4.2mg/kg	N/A	
		Dermal	N/A	N/A	4.2mg/kg	N/A	
		Inhalation	155.2mg/m ³	155.2mg/m ³	14.7mg/m ³	14.7mg/m ³	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9		Oral	N/A	N/A	36mg/kg	N/A	
		Dermal	N/A	N/A	320mg/kg	N/A	
		Inhalation	N/A	N/A	33mg/m ³	33mg/m ³	

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

	Identification	Short exposure		Long exposure		
		Systemic	Local	Systemic	Local	
8.1	Butanone CAS: 78-93-3 EC: 201-159-0	Oral	N/A	N/A	31mg/kg	N/A
		Dermal	N/A	N/A	412mg/kg	N/A
		Inhalation	N/A	N/A	106mg/m ³	N/A
	Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	N/A	N/A	4.5mg/kg	N/A
		Dermal	N/A	N/A	37mg/kg	N/A
		Inhalation	734mg/m ³	734mg/m ³	367mg/m ³	367mg/m ³
	Toluene CAS: 108-88-3 EC: 203-625-9	Oral	N/A	N/A	8.13mg/kg	N/A
		Dermal	N/A	N/A	226mg/kg	N/A
		Inhalation	226mg/m ³	226mg/m ³	56.5mg/m ³	56.5mg/m ³
	Fatty acids, tall-oil, compds. with oleylamine CAS: 85711-55-3 EC: 288-315-1	Oral	N/A	N/A	0.012mg/kg	N/A
		Dermal	N/A	N/A	0.012mg/kg	N/A
		Inhalation	N/A	N/A	N/A	N/A
	1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Oral	N/A	N/A	15mg/kg	N/A
		Dermal	N/A	N/A	9512mg/kg	N/A
		Inhalation	29.4mg/m ³	29.4mg/m ³	29.4mg/m ³	29.4mg/m ³
	Cumene CAS: 98-82-8 EC: 202-704-5	Oral	N/A	N/A	5mg/kg	N/A
		Dermal	N/A	N/A	1.2mg/kg	N/A
		Inhalation	N/A	N/A	16.6mg/m ³	N/A
Mesitylene CAS: 108-67-8 EC: 203-604-4	Oral	N/A	N/A	15mg/kg	N/A	
	Dermal	N/A	N/A	9512mg/kg	N/A	
	Inhalation	29.4mg/m ³	29.4mg/m ³	29.4mg/m ³	29.4mg/m ³	
Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	Oral	N/A	N/A	12.5mg/kg	N/A	
	Dermal	N/A	N/A	125mg/kg	N/A	
	Inhalation	260mg/m ³	260mg/m ³	65.3mg/m ³	65.3mg/m ³	
PNEC	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	STP	6.58mg/L	Fresh Water	0.327mg/L	
		Soil	2.31mg/kg	Marine Water	0.327mg/L	
		Intermittent	0.327mg/L	Sediment (FW)	12.46mg/kg	
		Oral	N/A	Sediment (MW)	12.46mg/kg	
	Toluene CAS: 108-88-3 EC: 203-625-9	STP	13.61mg/L	Fresh Water	0.68mg/L	
		Soil	0.09mg/kg	Marine Water	0.68mg/L	
		Intermittent	0.36mg/L	Sediment (FW)	16.39mg/kg	
		Oral	N/A	Sediment (MW)	16.39mg/kg	

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

8.1	PNEC	Identification				
		N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35.6mg/L	Fresh Water	0.18mg/L
			Soil	0.09mg/kg	Marine Water	0.018mg/L
			Intermittent	0.36mg/L	Sediment (FW)	0.981mg/kg
			Oral	Not Relevant	Sediment (MW)	0.098mg/kg
		4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	STP	27.5mg/L	Fresh Water	0.6mg/L
			Soil	1.3mg/kg	Marine Water	0.06mg/L
			Intermittent	1.5mg/L	Sediment (FW)	8.27mg/kg
			Oral	Not Relevant	Sediment (MW)	0.83mg/kg
		2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100mg/L	Fresh Water	0.635mg/L
			Soil	0.29mg/kg	Marine Water	0.064mg/L
			Intermittent	6.35mg/L	Sediment (FW)	3.29mg/kg
			Oral	Not Relevant	Sediment (MW)	0.329mg/kg
		Butanone CAS: 78-93-3 EC: 201-159-0	STP	709mg/L	Fresh Water	55.8mg/L
			Soil	22.5mg/kg	Marine Water	558mg/L
			Intermittent	55.8mg/L	Sediment (FW)	284.74mg/kg
			Oral	1g/kg	Sediment (MW)	284.7mg/kg
		Ethyl acetate CAS: 141-78-6 EC: 205-500-4	STP	650mg/L	Fresh Water	0.24mg/L
			Soil	0.148mg/kg	Marine Water	0.024mg/L
			Intermittent	1.65mg/L	Sediment (FW)	1.15mg/kg
			Oral	0.2g/kg	Sediment (MW)	0.115mg/kg
		Toluene CAS: 108-88-3 EC: 203-625-9	STP	13.61mg/L	Fresh Water	0.68mg/L
			Soil	2.89mg/kg	Marine Water	0.68mg/L
			Intermittent	0.68mg/L	Sediment (FW)	16.39mg/kg
			Oral	Not Relevant	Sediment (MW)	16.39mg/kg
		Fatty acids, tall-oil, compds. with oleylamine CAS: 85711-55-3 EC: 288-315-1	STP	Not Relevant	Fresh Water	Not Relevant
			Soil	Not Relevant	Marine Water	Not Relevant
			Intermittent	Not Relevant	Sediment (FW)	Not Relevant
			Oral	0.00047g/kg	Sediment (MW)	Not Relevant
		1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	STP	2.41mg/L	Fresh Water	0.12mg/L
			Soil	2.34mg/kg	Marine Water	0.12mg/L
			Intermittent	0.12mg/L	Sediment (FW)	13.56mg/kg
Oral	Not Relevant		Sediment (MW)	13.56mg/kg		
Cumene CAS: 98-82-8 EC: 202-704-5	STP	200mg/L	Fresh Water	0.035mg/L		
	Soil	0.624mg/kg	Marine Water	0.004mg/L		
	Intermittent	0.012mg/L	Sediment (FW)	3.22mg/kg		
	Oral	Not Relevant	Sediment (MW)	0.322mg/kg		

ULTRIMAX POLYURETHANE CLEAR LACQUER





HEALTH AND SAFETY DATA SHEET

Prepared in accordance to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

8.1	PNEC	Identification				
		Mesitylene CAS: 108-67-8 EC: 203-604-4	STP	2.02mg/L	Fresh Water	0.101mg/L
			Soil	1.34mg/kg	Marine Water	0.101mg/L
			Intermittent	0.101mg/L	Sediment (FW)	7.86mg/kg
			Oral	Not Relevant	Sediment (MW)	7.86mg/kg
		Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	STP	6.58mg/L	Fresh Water	0.327mg/L
			Soil	2.31mg/kg	Marine Water	0.327mg/L
			Intermittent	0.327mg/L	Sediment (FW)	12.46mg/kg
			Oral	Not Relevant	Sediment (MW)	12.46mg/kg
		8.2	Exposure controls	<p>Individual protection measures, such as personal protective equipment In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.</p> <p>All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.</p>		
Respiratory protection						
Pictogram	PPE			Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles				EN 149:2001+A1:2009 EN 405:2022+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.
Specific protection for the hands						
Pictogram	PPE	Labelling	CEN Standard	Remarks		
 Mandatory hand protection	Chemical protective gloves (material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.		
As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and is to be checked prior to the application.						

ULTRIMAX POLYURETHANE CLEAR LACQUER







HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

8.2	Exposure controls	Eye and face protection				
		Pictogram	PPE	Labelling	CEN Standard	Remarks
		 Mandatory face protection	Face Shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacture's instructions. Use if there is a risk of splashing.
		Body protection				
		Pictogram	PPE	Labelling	CEN Standard	Remarks
		 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
		 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties.		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace the boots at any sign of deterioration.
		Additional Emergency measures				
		Emergency measure	Standards	Emergency Measure	Standards	
		Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 38644:2011	
	Environmental exposure controls	In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D.				
	Volatile organic compounds	With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C (Supply): 66.55% weight V.O.C. density at 25°C: 624.33kg/m ³ (624.33 g/L) Average carbon number: 6.93 Average molecular weight: 104.97 g/mol				

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties		For complete information see the product datasheet	
9.1	Appearance	Physical state at 20°C	Liquid
		Appearance	Viscous
		Colour	Ochre
		Odour	N/A
		Odour Threshold	N/A*
	Volatility	Boiling point at atmospheric pressure	123°C
		Vapour pressure at 25°C	2592Pa
		Vapour pressure at 50°C	8756.19pa (8.76 Kpa)
		Evaporation rate at 25°C	N/A*
	Product description	Density at 25°C	938.2 kg/m ³
		Relative density at 25°C	0.938
		Dynamic viscosity at 25°C	N/A*
		Kinematic viscosity at 25°C	N/A*
		Kinematic viscosity at 40°C	>20.5mm ² /s
		Concentration	N/A*
		pH	N/A*
		Vapour density at 25 °C	N/A*
		Partition coefficient n-octanol/water 25 °C	N/A*
		Solubility in water at 25 °C	N/A*
		Solubility properties	N/A*
Decomposition temperature		N/A*	
Melting point/freezing point		N/A*	
Flammability	Flash point	25°C	
	Flammability (solid, gas)	N/A*	
	Autoignition temperature	200°C	
	Lower flammability limit	N/A*	
	Upper flammability limit	N/A*	
Particle characteristics	Median equivalent diameter	N/A	
9.2	Other information Information with regard to physical hazard classes	Explosive properties	N/A*
		Oxidising properties	N/A*
		Corrosive to metals	N/A*
		Heat of combustion	N/A*
		Aerosols-total percentage (by mass) of flammable components	N/A
	Other safety characteristics	Surface tension at 25°C	N/A*
Refraction index		N/A*	

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

10. STABILITY AND REACTIVITY

10.1	Reactivity	No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.	
10.2	Chemical stability	Chemically stable under the indicated conditions of storage, handling and use	
10.3	Possibility of hazardous reactions	Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected	
10.4	Conditions to avoid	Applicable for handling and storage at room temperature:	
		Shock and friction	N/A
		Contact with air	N/A
		Increase in temperature	Risk of Combustion
		Sunlight	Avoid Direct Impact
10.5	Incompatible materials	Acids	Avoid strong acids
		Water	N/A
		Oxidising materials	Avoid direct impact
		Combustible materials	N/A
		Others	Avoid alkalis or strong bases
10.6	Hazardous decomposition products	Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.	

11. TOXICOLOGICAL INFORMATION

11.1	Information on hazard classes as defined in Regulation (EC) No 1272/2008	The experimental information related to the toxicological properties of the product itself is not available.
	Dangerous health implications	In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits adverse effects of health may result, depending on the means of exposure:

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

11.1	Dangerous health implications	<p>Ingestion (acute effect):</p> <ul style="list-style-type: none"> Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3 Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
		<p>Inhalation (acute effect):</p> <ul style="list-style-type: none"> Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3. Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
		<p>Contact with the skin and the eyes (acute effect):</p> <ul style="list-style-type: none"> Contact with the skin: Produces skin inflammation Contact with the eyes: Produces eye damage after contact
		<p>CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):</p> <ul style="list-style-type: none"> Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2. IARC: Toluene (3); Reaction mass of ethylbenzene and xylene (3); Toluene (3); Cumene (2B); Solvent naphtha (petroleum), light aromatic (3); Naphtha (petroleum), hydrotreated heavy (3); Hydrocarbons, C9-C12,n-alkanes, isoalkanes, cyclics, aromatics (2-25%)(3); Polyethylene wax (3); Reaction mass of ethylbenzene and xylene (3); Hydrocarbons, C9, aromatics (3); propan-2-ol (3); 4-methylpentan-2-one (2B) Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3. Reproductive toxicity: Suspected of damaging the unborn child
		<p>Sensitizing effects</p> <ul style="list-style-type: none"> Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3. Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
		<p>Specific target organ toxicity (STOT) - single exposure</p> <ul style="list-style-type: none"> Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
		<p>Specific target organ toxicity (STOT)-repeated exposure</p> <ul style="list-style-type: none"> Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
		<p>Aspiration hazard</p> <p>Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.</p>

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

	Identification	Acute Toxicity		Genus
11.1 Specific toxicology information on the substances	2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532mg/kg	Rat
		LD50 dermal	>5000mg/kg	Rat
		LC50 inhalation	30mg/L (4h)	Rat
	Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580mg/kg	Rat
		LD50 dermal	12124mg/kg	Rat
		LC50 inhalation	28.1mg/L (4h)	Rat
	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	2100mg/kg	Rat
		LD50 dermal	1100mg/kg (ATEi)	Rat
		LC50 inhalation	11mg/L (4h)	Rat
	Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000mg/kg	Rat
		LD50 dermal	6400mg/kg	Rabbit
		LC50 inhalation	23.5mg/L (4h)	Rat
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789mg/kg	Rat
		LD50 dermal	14112mg/kg	Rabbit
		LC50 inhalation	23.4mg/L (4h)	Rat
	Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LD50 oral	4100mg/kg	Rat
		LD50 dermal	20000mg/kg	Rabbit
		LC50 inhalation	>20mg/L	
	4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	LD50 oral	>2000mg/kg	
		LD50 dermal	>200mg/kg	
LC50 inhalation		11mg/L(4h) (ATEi)	Rat	
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580mg/kg	Rat	
	LD50 dermal	12124mg/kg	Rat	
	LC50 inhalation	28.1mg/L (4h)	Rat	
Fatty acids, tall-oil, compds. with oleylamine CAS: 85711-55-3 EC: 288-315-1	LD50 oral	>2000mg/kg		
	LD50 dermal	>2000mg/kg		
	LC50 inhalation	>5mg/L		
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	LD50 oral	3400mg/kg	Rat	
	LD50 dermal	3160mg/kg	Rabbit	
	LC50 inhalation	11mg/L (4h)	Rat	
Cumene CAS: 98-82-8 EC: 202-704-5	LD50 oral	2700mg/kg		
	LD50 dermal	>2000mg/kg		
	LC50 inhalation	>20mg/L		

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

11.1	Specific toxicology information on the substances	Identification		Acute Toxicity		Genus		
		Mesitylene CAS: 108-67-8 EC: 203-604-4	LD50 oral	6000mg/kg	Rat			
			LD50 dermal	>2000mg/kg				
			LC50 inhalation	>20mg/L				
		1,2,3-trimethylbenzene CAS: 526-73-8 EC: 208-394-8	LD50 oral	>2000mg/kg				
			LD50 dermal	>2000mg/kg				
			LC50 inhalation	>20mg/L				
		Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	LD50 oral	2100mg/kg	Rat			
			LD50 dermal	1100mg/kg	Rat			
			LC50 inhalation	11mg/L (4h)	Rat			
		11.2	Information on other hazards	Endocrine-disrupting properties: The product does not meet the criteria				
			Endocrine disrupting properties					
Other information	N/A							

12. ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available.

Harmful to aquatic life with long lasting effects.

12.1	Acute toxicity	Toxicity		Identification	Concentration	Species	Genus
		Reaction mass of ethylbenzene and xylene CAS: N/A EC: 905-588-0	LC50	>10-100mg/L (96h)		Fish	
			EC50	>10-100mg/L (48h)		Crustacean	
			EC50	>10-100mg/L (72h)		Algae	
		Toluene CAS: 108-88-3 EC: 203-625-9	LC50	13mg/L (96h)	Carassius auratus	Fish	
			EC50	11.5mg/L (48h)	Daphnia magna	Crustacean	
			EC50	N/A			
		N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	N/A			
			EC50	N/A			
			EC50	675mg/L (72h)	Scenedesmus subspicatus	Algae	
		4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	LC50	900mg/L (96h)	Leuciscus idus	Fish	
			EC50	862mg/L (24h)	Daphnia magna	Crustacean	
			EC50	980mg/L (48h)	Scenedesmus subspicatus	Algae	
		2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50	161mg/L (96h)	Pimephales promelas	Fish	
			EC50	481mg/L (48h)	Daphnia sp.	Crustacean	
			EC50	N/A			

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

Toxicity	Identification	Concentration		Species	Genus
12.1 Acute toxicity	Butanone CAS: 78-93-3 EC: 201-159-0	LC50	3220mg/L (96h)	Pimephales promelas	Fish
		EC50	5091mg/L (48h)	Daphnia magna	Crustacean
		EC50	4300mg/L (168h)	Scenedesmus quadricauda	Algae
	Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
		EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
		EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
	Toluene CAS: 108-88-3 EC: 203-625-9	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
		EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
		EC50	N/A		
	1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	LC50	7,72 mg/L (96 h)	Pimephales promelas	Fish
		EC50	6,14 mg/L (48 h)	Daphnia magna	Crustacean
		EC50	N/A		
	Cumene CAS: 98-82-8 EC: 202-704-5	LC50	2,7 mg/L (96 h)	Salmo gairdneri	Fish
		EC50	10,8 mg/L (48 h)	Daphnia magna	Crustacean
		EC50	2,6 mg/L (72 h)	Selenastrum capricornutum	Algae
	Mesitylene CAS: 108-67-8 EC: 203-604-4	LC50	12,5 mg/L (96 h)	Carassius auratus	Fish
		EC50	50 mg/L (24 h)	Daphnia magna	Crustacean
		EC50	53 mg/L (48 h)	Scenedesmus subspicatus	Algae
Chronic toxicity	Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
		NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Not relevant		
		NOEC	23,2 mg/L	Daphnia magna	Crustacean
	4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	NOEC	Not relevant		
		NOEC	78 mg/L	Daphnia magna	Crustacean
	2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
		NOEC	100 mg/L	Daphnia magna	Crustacean

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

Toxicity		Identification	Concentration		Species	Genus		
12.1	Chronix toxicity	Ethyl acetate CAS: 141-78-6 EC: 205-500-4	NOEC	9,65 mg/L	Pimephales promelas	Fish		
			NOEC	2,4 mg/L	Daphnia magna	Crustacean		
		Cumene CAS: 98-82-8 EC: 202-704-5	NOEC	0,38 mg/L	Pimephales promelas	Fish		
			NOEC	0,35 mg/L	Daphnia magna	Crustacean		
		Mesitylene CAS: 108-67-8 EC: 203-604-4	NOEC	0,277 mg/L	N/A	Fish		
			NOEC	0,4 mg/L	Daphnia magna	Crustacean		
		Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish		
			NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean		
		Persistence and degradability		Identification	Degradability		Biodegradability	
12.2	Substance-specific information	Toluene CAS: 108-88-3 EC: 203-625-9	BOD5	2,5 g O2/g	Concentration	100 mg/L		
			COD	N/A	Period	14 days		
			BOD5/COD	N/A	% Biodegradable	100 %		
		N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	N/A	Concentration	N/A		
			COD	N/A	Period	5 days		
			BOD5/COD	N/A	% Biodegradable	84 %		
		4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	BOD5	2,06 g O2/g	Concentration	100mg/L		
			COD	2,16 g O2/g	Period	14 days		
			BOD5/COD	0,95	% Biodegradable	84 %		
		2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	N/A	Concentration	785mg/L		
			COD	N/A	Period	8 days		
			BOD5/COD	Not relevant	% Biodegradable	100 %		
		Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2,03 g O2/g	Concentration	N/A		
			COD	2,31 g O2/g	Period	20 days		
			BOD5/COD	0,88	% Biodegradable	89 %		
		Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BOD5	1,36 g O2/g	Concentration	100 mg/L		
			COD	1,69 g O2/g	Period	14 days		
			BOD5/COD	0,8	% Biodegradable	83 %		
		Toluene CAS: 108-88-3 EC: 203-625-9	BOD5	2,5 g O2/g	Concentration	100 mg/L		
			COD	N/A	Period	14 days		
			BOD5/COD	N/A	% Biodegradable	100 %		
		1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	BOD5	N/A	Concentration	100 mg/L		
			COD	N/A	Period	28 days		
			BOD5/COD	N/A	% Biodegradable	18 %		

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

12.2	Substance-specific information	Identification	Degradability		Biodegradability	
		Cumene CAS: 98-82-8 EC: 202-704-5	BOD5	N/A	Concentration	100 mg/L
		COD	N/A	Period	14 days	
		BOD5/COD	N/A	% Biodegradable	40 %	
	Mesitylene CAS: 108-67-8 EC: 203-604-4	BOD5	N/A	Concentration	100 mg/L	
		COD	N/A	Period	14 days	
		BOD5/COD	N/A	% Biodegradable	0 %	
12.3	Substance-specific information	Identification	Bioaccumulation potential			
		Reaction mass of ethylbenzene and xylene CAS: N/A EC: 905-588-0	BCF	9		
			Pow Log	2.77		
			Potential	Low		
	Toluene CAS: 108-88-3 EC: 203-625-9	BCF	90			
		Pow Log	2.73			
		Potential	Low			
	N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4			
		Pow Log	1.78			
		Potential	Low			
	4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	BCF	2			
		Pow Log	1.31			
		Potential	Low			
	2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1			
		Pow Log	0.43			
		Potential	Low			
	Butanone CAS: 78-93-3 EC: 201-159-0	BCF	3			
		Pow Log	0.29			
		Potential	Low			
	Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BCF	30			
		Pow Log	0.73			
		Potential	Moderate			
	Toluene CAS: 108-88-3 EC: 203-625-9	BCF	90			
		Pow Log	2.73			
		Potential	Moderate			
	1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	BCF	154			
		Pow Log	3.78			
		Potential	High			

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

12.3	Substance-specific information	Identification		Bioaccumulation potential					
		Cumene CAS: 98-82-8 EC: 202-704-5	BCF	120					
			Pow Log	3.66					
			Potential	High					
		Mesitylene CAS: 108-67-8 EC: 203-604-4	BCF	182					
			Pow Log	3.42					
			Potential	High					
		Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0	BCF	9					
			Pow Log	2.77					
			Potential	Low					
		12.4	Mobility in soil	Identification		Absorption/desorption		Volatility	
				Toluene CAS: 108-88-3 EC: 203-625-9	Koc	178		Henry	672,8 Pa·m ³ /mol
Conclusion	Moderate				Dry Soil	Yes			
Surface Tension	2,793E-2 N/m (25°C)				Moist Soil	Yes			
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc			Not relevant		Henry	Not relevant		
	Conclusion			Not relevant		Dry Soil	Not relevant		
	Surface Tension			2,478E-2 N/m (25°C)		Moist Soil	Not relevant		
4-methylpentan-2-one CAS: 108-10-1 EC: 203-550-1	Koc			Not relevant		Henry	Not relevant		
	Conclusion			Not relevant		Dry Soil	Not relevant		
	Surface Tension			2,35E-2 N/m (25 °C)		Moist Soil	Not relevant		
Butanone CAS: 78-93-3 EC: 201-159-0	Koc			30		Henry	5,77 Pa·m ³ /mol		
	Conclusion			Very High		Dry Soil	Yes		
	Surface Tension			2,396E-2 N/m (25°C)		Moist Soil	Yes		
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Koc			59		Henry	13,58Pa·m ³ /mol		
	Conclusion			Very High		Dry Soil	Yes		
	Surface Tension			2,324E-2 N/m (25°C)		Moist Soil	Yes		
Toluene CAS: 108-88-3 EC: 203-625-9	Koc			178		Henry	672,8Pa·m ³ /mol		
	Conclusion			Moderate		Dry Soil	Yes		
	Surface Tension			2,793E-2 N/m (25°C)		Moist Soil	Yes		
1,2,4-trimethylbenzene CAS: 95-63-6 EC: 202-436-9	Koc			537		Henry	624,16 Pa·m ³ /mol		
	Conclusion			Low		Dry Soil	Yes		
	Surface Tension			2,919E-2 N/m (25°C)		Moist Soil	Yes		

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

12.4	Mobility in soil	Identification	Absorption/desorption		Volatility	
		Cumene CAS: 98-82-8 EC: 202-704-5	Koc	Not relevant	Henry	Not relevant
Conclusion	Not relevant		Dry Soil	Not relevant		
Surface Tension	2,769E-2 N/m (25°C)		Moist Soil	Not relevant		
Mesitylene CAS: 108-67-8 EC: 203-604-4	Koc	1445	Henry	888,62 Pa·m ³ /mol		
	Conclusion	Low	Dry Soil	Yes		
	Surface Tension	2,805E-2 N/m (25°C)	Moist Soil	Yes		
1,2,3-trimethylbenzene CAS: 526-73-8 EC: 208-394-8	Koc	Not relevant	Henry	Not relevant		
	Conclusion	Not relevant	Dry Soil	Not relevant		
	Surface Tension	3,075E-2 N/m (25°C)	Moist Soil	Not relevant		
12.5	Results of PBT and vPvB assessment	Product does not meet PBT/vPvB criteria				
12.6	Endocrine disrupting properties	Endocrine-disrupting properties: The product does not meet the criteria				
12.7	Other adverse effects	Not described				

13. DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	Code	Description	Waste Class (Regulation (EU) No 1357/2014)
		08 01 11*	Waste paint and varnish containing organic solvents or other hazardous substances	Hazardous
	Type of waste (Regulation (EU) No 1357/2014)	HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP7 Carcinogenic, HP10 Toxic for reproduction, HP4 Irritant— skin irritation and eye damage.		
	Waste management (disposal and evaluation)	Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.		
	Regulations related to waste management	In accordance with Annex II of Regulation (EC) No 1907/2006(REACH) the community or state provisions related to waste management are stated Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014.		

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

14. TRANSPORT INFORMATION

		Transport of dangerous goods by land With regard to ADR 2023 and RID 2023	Transport of dangerous goods by sea With regard to IMDG 40-20	Transport of dangerous goods by air With regard to IATA/ICAO 2023
14.1	UN number or ID number	UN1263	UN1263	UN1263
14.2	UN proper shipping name	PAINT	PAINT	PAINT
14.3	Transport hazard class(es)	3	3	3
	Labels	3	3	3
14.4	Packing group	III	III	III
14.5	Environmental hazards	No	No	No
14.6	Special precautions for user			
	Special regulations	163, 367, 650	223, 955, 163, 367	
	EmS Codes		F-E, S-E	
	Tunnel restriction code	D/E		see section 9
	Physico-Chemical properties	see section 9	see section 9	
14.7	Limited quantities	5L	5L	
	Segregation Group		Not Relevant	
14.7	Maritime transport in bulk according to IMO instruments	Not Relevant	Not Relevant	Not Relevant

15. REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	<ul style="list-style-type: none"> Article 95, REGULATION (EU) No 528/2012: Not relevant Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant 									
	Seveso III	<table border="1"> <thead> <tr> <th>Section</th> <th>Description</th> <th>Lower-tier requirements</th> <th>Upper-tier requirements</th> </tr> </thead> <tbody> <tr> <td>P5c</td> <td>FLAMMABLE LIQUIDS</td> <td>5000</td> <td>50000</td> </tr> </tbody> </table>	Section	Description	Lower-tier requirements	Upper-tier requirements	P5c	FLAMMABLE LIQUIDS	5000	50000	
Section	Description	Lower-tier requirements	Upper-tier requirements								
P5c	FLAMMABLE LIQUIDS	5000	50000								

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

15.1	Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc...)	<p>Shall not be used in:</p> <ul style="list-style-type: none"> • ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays • tricks and jokes • games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. 2. For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.' Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.
	Specific provisions in terms of protecting people or the environment	It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.
	Other legislation	The product could be affected by sectorial legislation
15.2	Chemical safety assessment	The supplier has not carried out evaluation of chemical safety

16. OTHER INFORMATION

Legislation related to safety data sheets	The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).
Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks	<p>COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):</p> <ul style="list-style-type: none"> • Removed substances <ul style="list-style-type: none"> ◦ Reaction mass of ethylbenzene and m-xylene and p-xylene <p>Substances that contribute to the classification (SECTION 2)</p> • New declared substances <ul style="list-style-type: none"> ◦ Propyl acetate (109-60-4) • Removed substances <ul style="list-style-type: none"> ◦ Reaction mass of ethylbenzene and m-xylene and p-xylene <p>CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16)</p> • Hazard statements

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

<p>Texts of the legislative phrases mentioned in section 2</p>	<p>H336: May cause drowsiness or dizziness. H335: May cause respiratory irritation. H315: Causes skin irritation. H373: May cause damage to organs through prolonged or repeated exposure. H412: Harmful to aquatic life with long lasting effects. H361d: Suspected of damaging the unborn child. H351: Suspected of causing cancer. H226: Flammable liquid and vapour. H319: Causes serious eye irritation.</p>
<p>Texts of the legislative phrases mentioned in section 3</p>	<p>The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3.</p>
<p>CLP regulation (EC) no 1272/2008</p>	<p>Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled. Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Carc. 1B: H350 - May cause cancer. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1A: H317 - May cause an allergic skin reaction. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation). STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H335 - May cause respiratory irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.</p>
<p>Classification procedure</p>	<p>STOT SE 3: Calculation method STOT SE 3: Calculation method Skin Irrit. 2: Calculation method STOT RE 2: Calculation method Aquatic Chronic 3: Calculation method Repr. 2: Calculation method Carc. 2: Calculation method Flam. Liq. 2: Calculation method (2.6.4.3) Eye Irrit. 2: Calculation method</p>
<p>Advice related to training</p>	<p>Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.</p>

ULTRIMAX POLYURETHANE CLEAR LACQUER

HEALTH AND SAFETY DATA SHEET

Prepared in according to 29 CFR 1910.1200

Date of compilation: 03/10/2019

Revised Date: 07/06/2024

Version: 11

Principal bibliographical sources	http://echa.europa.eu http://eur-lex.europa.eu
Abbreviations and acronyms	ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer