

ULTRIMAX

Road Marking Paint

HEALTH AND SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006,(REACH).
Revision date: 08-Dec-20
Version: 4.60

Page 1

1. PRODUCT AND COMPANY IDENTIFICATION

1.01 Product Code	Ultrimax Road Marking Paint
1.02 Manufacturer/Supplier	Ultrimax Coatings Ltd
1.03 Address	Shaw Lane Industrial Estate, Ogden Road, Doncaster, DN2 4SE
1.04 Contact	www.ultrimaxcoatings.co.uk
1.05 Phone Number	01302 856666
1.06 Fax Number	01302 571510
1.7 Emergency Phone Number	01302 856666

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008, (CLP)

Flammable Liquids, Category 2	H225 Highly flammable liquid and vapour.
Skin Irritation, Category 2	H315 Causes skin irritation.
Eye Irritation, Category 2	H319 Causes serious eye irritation.
Specific Target Organ Toxicity, Single Exposure, Category 3	H336 May cause drowsiness or dizziness.
Reproductive Toxicity, Category 2	H361d Suspected of damaging the unborn child.
Specific Target Organ Toxicity, Repeated Exposure, Category 2	H373 May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008, (CLP)

Hazard pictograms

Signal Word DANGER

Hazard pictograms



Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust, fume, gas, mist, vapours or spray.
P280 Wear protective gloves, protective clothing, eye protection and face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice or attention.
P403+P235 Store in a well-ventilated place. Keep cool.
Supplemental hazard information: EUH208 Contains 2-butanone oxime. May produce an allergic reaction.

Other hazards

Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

ULTRIMAX

Road Marking Paint

HEALTH AND SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006,(REACH).
Revision date: 08-Dec-20
Version: 4.60

Page 2

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

Description of the mixture : Mixture of resins, solvents,pigments and additives.

Chemical name	EC Number	CAS Number	Reach registration Number	% weight	Classification [Regulation (EC) No. 1272/2008]
Toluene	203-625-9	108-88-3	01-2119471310-51	10%-25%	H225, H304, H315, H336, H361d, H373
Xylene	215-535-7	1330-20-7	01-2119488216-32	2.5%-10%	H226, H304, H312, H315, H319, H332, H335, H373
Ethylbenzene	202-849-4	100-41-4	01-2119489370-35	<4%	H225, H304, H332, H373
2-butanone oxime	202-496-6	96-29-7	01-2119539477-28	0.1%-1.0%	H312, H317, H318, H351

Addition information: For the full text of the Hazard Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
If inhaled :	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact :	Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
In case of eye contact :	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
If swallowed :	If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Self-protection of the first aider :	None.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3 Indication of any immediate medical attention and special treatment needed

None

ULTRIMAX

Road Marking Paint

HEALTH AND SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006,(REACH).
Revision date: 08-Dec-20
Version: 4.60

Page 3

5. FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, CO2, powders and water spray/mist.
Unsuitable extinguishing media : Water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products : Fire will produce dense black smoke.
Exposure to decomposition products may cause a health hazard.
Appropriate breathing apparatus may be required.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire with water.
Do not allow run-off from fire fighting to enter drains or watercourses.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area.
Avoid breathing vapours.
Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or watercourses.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see Section 13).
Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

None

ULTRIMAX

Road Marking Paint

HEALTH AND SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006,(REACH).
Revision date: 08-Dec-20
Version: 4.60

Page 4

7. HANDLING & STORAGE

7.1. Precautions for safe handling

Advice on safe handling:

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear anti-static footwear and clothing and floors should be of the conducting type.

Isolate from sources of heat, sparks and open flame.

No sparking tools should be used.

Avoid skin and eye contact.

Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture.

Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

Advice on protection against fire and explosion:

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers:

Store in accordance with the Dangerous Substances and Explosive Atmospheres Regulations, 2002, (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.

Notes on joint storage:

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Additional information on storage conditions:

Observe label precautions.

Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition.

No smoking.

Prevent unauthorised access.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

The principles contained in the HSE guidance note,

Chemical Warehousing: The Storage of Packaged

Dangerous Substances, should be observed when storing this product.

7.3 Specific end use(s) None.

ULTRIMAX

Road Marking Paint

HEALTH AND SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006,(REACH).
Revision date: 08-Dec-20
Version: 4.60

Page 5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Limits for occupational exposure and/or biological limit values.

Chemical name	LTEL - 8hr		TWA STEL - 15min		Notes
	ppm	mg/m	ppm	mg/m	
Toluene	50	191	100	384	Sk
Xylene	50	220	100	441	Sk, BMGV
Ethylbenzene	100	441	125	552 Sk	
2-butanone oxime	3	10	10	33	NAOSH(Ire)

LTEL - Long Term Exposure Limit, STEL - Short Term Exposure Limit, TWA - Time-Weighted Average.

ppm - parts per million by volume, mg/m³ - milligrams per cubic metre.

BMGV - Biological Monitoring Guidance Values are given in Table 2 of EH40/2005 Workplace exposure limits.

Carc - Capable of causing cancer and/or heritable genetic damage.

Sen - Capable of causing occupational asthma.

Sk - Can be absorbed through the skin. Dermal absorption may lead to systemic toxicity.

8.2. Exposure controls

8.2.1 Appropriate engineering controls

General advice

Provide adequate ventilation.

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

8.2.2 Personal protection equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling, use Polyvinyl Alcohol (PVA) or Viton Rubber (FluorRubber).

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Skin protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

8.2.3 Environmental exposure controls

General advice: Do not allow to enter drains or watercourses.

ULTRIMAX

Road Marking Paint

HEALTH AND SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006,(REACH).
Revision date: 08-Dec-20
Version: 4.60

Page 6

9. PHYSICAL & CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance - Physical state		Viscous liquid.
Colour :		Various.
Odour :		Aromatic hydrocarbons.
Odour threshold	Lower	Not determined.
	Higher	Not determined.
pH :		Not determined.
Melting point/freezing point (°C) :		>-39.3
Initial boiling point and boiling range (°C) :		110-140
Flash point (°C) :		4
Evaporation rate :		Not determined.
Flammability/explosive limits : Lower (%)		Not determined.
	Higher (%)	Not determined.
Vapour pressure :		>0.3 kPa
Vapour density (air=1) :		Heavier than air.
Relative density (g/ml) :		1.44-1.52
Solubility(ies)		Miscible with organic solvents.
Partition coefficient		2.65-3.20 log Pow
Auto-ignition temperature (°C)		>480
Decomposition temperature (°C)		2.6-2.8 poise.
Viscosity :		Not determined.
Explosive properties :		May form explosive mixtures with air.
Oxidising properties :		Not determined.

9.2. Other information

None

10. STABILITY & REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under recommended storage and handling conditions. (See Section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Carbon monoxide and dioxide, smoke, oxides of nitrogen.

ULTRIMAX

Road Marking Paint

HEALTH AND SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006,(REACH).
Revision date: 08-Dec-20
Version: 4.60

Page 7

11. TOXICOLOGICAL INFORMATION

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Classification, Labelling and Packaging of Substances and Mixtures Regulation (EC) No. 1272/2008, (CLP) and classified for toxicological hazards accordingly.

See Sections 2 and 3 for details.

11.1 Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhoea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

12. ECOLOGICAL INFORMATION

12.1. Toxicity

No data available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

The European List of Waste classification of this product, when disposed of as waste, is
Do not allow to enter drains or watercourses.

Waste Code: Name of Waste (according to Commission Decision 2000/532/EC):

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

14. TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Paint

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

IMDG Class 3

ICAO Class/Division 3



Transport Labels

14.4. Packing group

ADR/RID/ADN Packing group II

IMDG Packing group II

ICAO Packing group II

14.5. Environmental hazards

None

14.6. Special precautions for user

ADR Tunnel Restriction Code

IMDG EmS

IMDG Stowage Category

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Statutory Instruments

The information in this Safety Data Sheet is required pursuant to :

Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No. 1907/2006, (REACH).

Classification, Labelling and Packaging of substances and mixtures, Regulation (EC) No. 1272/2008, (CLP).

The Dangerous Substances and Explosive Atmospheres Regulations, 2002, (DSEAR).

- The Control of Substances Hazardous to Health Regulations, 2002, (COSHH).

- The Health and Safety at Work etc Act, 1974, (HSWA).

Approved Codes of Practice and Guidance notes relevant to this Safety Data Sheet :

- The European Chemicals Agency (ECHA) Guidance on the compilation of safety data sheets, Version 2.1.

- CEPE Guideline for Safety Data Sheets, 9th Edition.

- HSE Approved Code of Practice and Guidance, Dangerous Substances and Explosive Atmospheres.

- HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances.

- HSE publication, EH40/2005 Workplace exposure limits.

16. OTHER INFORMATION

Full text of Hazard Statements referred to in Section 3.

H225 : Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H336 : May cause drowsiness or dizziness.

H351 : Suspected of causing cancer.

H361d : Suspected of damaging the unborn child.

H373 : May cause damage to organs through prolonged or repeated exposure.

Legal disclaimer: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for his own particular use.