

# ULTRIMAX PERFORMANCE MASKING TAPE

## TECHNICAL DATA

| FEATURES                |   |
|-------------------------|---|
| Typical Applications    | Masking tape suitable for 80°C 1 hour oven baking in car Paint Workshops.<br>Also for miscellaneous industrial, construction and other painting applications. |
| Advantages and Benefits | Premium Water Resist paper  |
|                         | Excellent adhesion to all surfaces  |
|                         | Easy application on curved profiles and irregular surfaces  |
|                         | Easy removal  |
|                         | No residue  |
|                         | Compatible with solvent based paints and most water based paints  |
|                         | 80°C 1 hour temperature service   |
| Construction            | Backing: Saturated Water Resistant crepe paper  |
|                         | Adhesive: Natural rubber and hydrocarbon resins   |
|                         | Available Colour: Blue  |
| Technical Data          | Paper Grammage 70 Gsm   |
|                         | Total Thickness 145 Micron  |
|                         | Peel Adhesion 2,7 N/cm  |
|                         | Tensile Strength 42 N/cm  |
|                         | Elongation at break 10%   |
|                         | Temperature resistance 80°C 1 hour  |

Physical and performance characteristics shown above are obtained following tests recommended by Ultrimax. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

### Storage

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.