

# ULTRIMAX PERFORMANCE MASKING TAPE

## TECHNICAL DATA

FEATURES	
Typical Applications	Masking tape suitable for 80°C 1 hour oven baking in Paint Workshops.
Advantages and Benefits	Excellent adhesion to all surfaces
	Easy application on curved profiles and irregular surfaces
	Easy removal
	No residue
	Compatible with solvent based paints and most water based paints
	80°C 1 hour temperature service
Construction	Backing: Saturated crepe paper
	Adhesive: Natural rubber and hydrocarbon resins.
	Colour: Ivory
Technical Data	Paper Thickness 90 Micron
	Total Thickness 132 Micron
	Peel Adhesion 2,7 N/cm
	Tensile Strength 34 N/cm
	Elongation at break 10%
	Temperature resistance 80°C 1 hour

Physical and performance characteristics shown above are obtained following tests recommended by Ultrimax. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

### Storage

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.