

Technical Data Sheet

XA4009/00

MATTING PASTE FOR WATERBORNE SYSTEMS

Supersedes previous issue dated 10/23/96

DATE 10/28/09

Area of use:	To be added to clear or pigmented waterbased topcoat to increase matt level.	
Dosage:	from 1% to 10%;	approximately
	from 50 to 40 gloss	1%
	from 40 to 30 gloss	3%
	from 30 to 20 gloss	5%
	from 20 to 10 gloss	10%

Technical characteristics:

Solids content (%):	26 ± 1
Specific gravity (kg/l):	1.115 ± 0.030
Shelf-life (months):	6

General characteristics

XA4009/00 is a matting paste to be added to waterborne topcoats in order to adjust gloss level.

To ensure even matting, XA4009/00 is to be added under stirring conditions.

Warning

A percentage higher than the dosage recommended may jeopardise the elasticity of the topcoat for exteriors, thus causing cracks in the dry coating film.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.