

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : HYDRO WATERBORNE BASECOAT PIGMENTED BY SPRAY - white

Product code : AUL3396/13

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Paint or paint related material.
: Industrial use only.

1.3 Details of the supplier of the safety data sheet

SHERWIN-WILLIAMS Italy S.r.l.

Via del Fiffo, 12 - 40065 Pianoro (BO)

Italia - C.P. 18

Cod. Fisc. e Reg. Impr. Bo 08866930152

e-mail address of person responsible for this SDS : regulatory.SWI@sherwin.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : 0844 892 0111

Supplier

Telephone number : +39 051 770511

Hours of operation : Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Classification according to Directive 1999/45/EC [DPD]

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Not classified.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

HYDRO WATERBORNE BASECOAT PIGMENTED BY SPRAY - white

AUL3396/13

SECTION 2: Hazards identification

Supplemental label elements : Safety data sheet available on request.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Not applicable.

Biocidal products regulation

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
Butoxypropanol	REACH #: 01-2119475527-28 EC: 225-878-4 CAS: 5131-66-8 Index: 603-052-00-8	>=1 - <5	Xi; R36/38	Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1]
2-(2-Butoxyethoxy)-ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	>=1 - <5	Xi; R36 See Section 16 for the full text of the R-phrases declared above.	Eye Irrit. 2, H319 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

SECTION 4: First aid measures

- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, carbon dioxide, powders.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

: Due to the organic solvents content of the mixture:

Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Information on fire and explosion protection

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

HYDRO WATERBORNE BASECOAT PIGMENTED BY SPRAY - white

AUL3396/13

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorized access.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Contaminated absorbent material may pose the same hazard as the spilled product.

Store above 5°C (42°F) Protect from frost.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-Butoxyethoxy)-ethanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 10 ppm 8 hours. TWA: 67.5 mg/m ³ 8 hours. STEL: 15 ppm 15 minutes. STEL: 101.2 mg/m ³ 15 minutes.

Recommended monitoring procedures

- : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- : Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

- Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.
- : Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

- Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

Skin protection

Hand protection

Gloves

- : Wear suitable gloves tested to EN374.
- : Short Term Exposure less than 10 minutes Continuous use Nitrile gloves.
Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time) .
There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
The breakthrough time must be greater than the end use time of the product.
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Always ensure that gloves are free from defects and that they are stored and used correctly.
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personnel should wear protective clothing.

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Respiratory protection** : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

- Environmental exposure controls** : Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Not available.
Odor	: Paint
Odor threshold	: Not Available (Not Tested).
pH	: 7.6
Melting point/freezing point	: Not Available (Not Tested).
Initial boiling point and boiling range	: 100°C
Flash point	: Closed cup: >93.3°C
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability (solid, gas)	: Not Available (Not Tested).
Burning time	: Not Available (Not Tested).
Burning rate	: Not Available (Not Tested).
Upper/lower flammability or explosive limits	: Lower: 0.6% Upper: 20.4%
Vapor pressure	: 0.31 kPa [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 1.42
Solubility(ies)	: Not Available (Not Tested).
Solubility in water	: Not Available (Not Tested).
Partition coefficient: n-octanol/water	: Not Available (Not Tested).
Auto-ignition temperature	: Not Available (Not Tested).
Decomposition temperature	: Not Available (Not Tested).
Viscosity	: Kinematic (room temperature): >0.07 cm ² /s Kinematic (40°C): >0.205 cm ² /s
Explosive properties	
Oxidizing properties	: Under normal conditions of storage and use, hazardous reactions will not occur.

9.2 Other information

Heat of combustion : 0.0000034 kJ/g

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

HYDRO WATERBORNE BASECOAT PIGMENTED BY SPRAY - white

AUL3396/13

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butoxypropanol 2-(2-Butoxyethoxy)-ethanol	LD50 Dermal	Rabbit	3100 mg/kg	-
	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-

Acute toxicity estimates

No data available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-Butoxyethoxy)-ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-

Conclusion/Summary : Not available.

Sensitization

No data available

Conclusion/Summary : Not available.

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
No data available			

Specific target organ toxicity (repeated exposure)

HYDRO WATERBORNE BASECOAT PIGMENTED BY SPRAY - white

AUL3396/13

SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
No data available			

Aspiration hazard

Product/ingredient name	Result
No data available	

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Product/ingredient name	Result	Species	Exposure
2-(2-Butoxyethoxy)-ethanol	Acute LC50 1300000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
No data available				

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-(2-Butoxyethoxy)-ethanol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
No data available			

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.
: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : No.

European waste catalogue (EWC) : 08 01 12 waste paint and varnish other than those mentioned in 08 01 11

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

European waste catalogue (EWC) : Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06.

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	<u>Special provisions</u> Not Applicable	<u>Emergency schedules (EmS)</u> Not Applicable	<u>Special provisions</u> Not Applicable

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

HYDRO WATERBORNE BASECOAT PIGMENTED BY SPRAY - white

AUL3396/13

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

European Directive 2004/42/EC : EU limit value for this product (A/e): 400 g/L (2010). This product contains max VOC: 400 g/L

Seveso II Directive

This product is not controlled under the Seveso II Directive.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

International regulations

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number

SECTION 16: Other information

Key literature references and sources for data : vPvB = Very Persistent and Very Bioaccumulative
 : Regulation (EC) No. 1272/2008 [CLP]
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 DPD = Dangerous Preparations Directive [1999/45/EC]
 DSD = Dangerous Substances Directive [67/548/EEC]
 IATA = International Air Transport Association
 IMDG = International Maritime Dangerous Goods
 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010
 Directive 96/82/EC, and relative amendments & additions
 Directive 2008/98/EC, and relative amendments & additions
 Directive 2000/39/EC, and relative amendments & additions
 CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements : H315 Causes skin irritation.
 H319 Causes serious eye irritation.

Full text of classifications [CLP/GHS] : Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2

Full text of abbreviated R phrases : R36- Irritating to eyes.
 R36/38- Irritating to eyes and skin.

Full text of classifications [DSD/DPD] : Xi - Irritant

Date of printing : 24, Apr, 2015.

Date of issue/ Date of revision : 24, Apr, 2015.

Date of previous issue : No previous validation.
 : If there is no previous validation date please contact your supplier for more information.

Version : 1

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.