

ULTRIMAX

Clear MDF Sealer

TECHNICAL DATA

PRODUCT DESCRIPTION	A nitrocellulose based clear basecoat used to seal solid wood and veneers in the production of furniture and related items. The addition of an additive ensures good sanding properties.
FEATURES	For use as a basecoat only.
RECOMMENDED USE	Most wood substrates.
PHYSICAL PROPERTIES	MIXING RATIO: n/a COLOUR: Clear GLOSS: Sealer VISCOSITY: 45-50 sec B4 @ 20°C VOC CONTENT: approx 666 gms/ltr WEIGHT SOLIDS: 29% FLASH POINT: Below 22°C POT LIFE: n/a COVERAGE: 8-10 square metres per ltr
FILM THICKNESS	WET FILM THICKNESS: 100 microns DRY FILM THICKNESS: 20-25 microns
SURFACE PREPARATION	Ensure surfaces are clean, dry and free from dust or other contamination.
APPLICATION METHODS	1 or 2 coats by conventional spray application onto most wood substrates. Too many coats can cause cracking. Use thinner if being used on MDF and check drying before use.
STORAGE LIFE	12 months from manufacture date.
DRYING / OVERCOATING	Touch dry 20 mins. Sanding is normally possible after 30 mins. CURING TIMES: n/a
THINNERS	Ultrimax Thinners.
HEALTH & SAFETY	Please refer to the material safety data sheets for further information.

The information in this data sheet is correct, to the best of our knowledge, based on laboratory tests and practical experience. However, as the product is used under conditions which are beyond our control, we cannot guarantee anything but the quality of the product itself. We recommend that users carry out tests to satisfy themselves with the suitability of the product for its intended use. These details are subject to revision from time to time, without notice.